

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Flam. Liq. 3; H226

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:  
Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP  
Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Warning

**Hazardous component(s) to be indicated on label:**

1-methoxy-2-propanol

**Hazard statement(s)**

H226

Flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

**Precautionary statement(s)**

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271

Use only outdoors or in a well-ventilated area.

P370+P378

In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

P501

Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	<b>1-methoxy-2-propanol</b>		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034	Flam. Liq. 3; H226 STOT SE 3; H336	>= 70.00 - < 90.00 wt%
2	<b>hydrogen tris[[[3-[(2-ethylhexyl)oxy]propyl]amino]sulphonyl]-29H,31H phthalocyaninesulphonato(3-)-N-{29}-,N-{30}-,N-{31}-,N-{32}]cuprate(1-), compound with 3-[(2-ethylhexyl)oxy]propylamine (1:1) C.I. Solvent Blue 70</b>		
	94277-77-7 304-661-9 - -	Aquatic Chronic 3; H412	< 5.00 wt%
3	<b>9-[2-(ethoxycarbonyl)phenyl]-3,6-bis(ethylamino)-2,7 dimethylxanthylum ethyl sulphate</b>		
	26694-69-9 247-906-4 - 01-2119935914-30-	Acute Tox. 4; H302 Aquatic Acute 1; H400 Eye Dam. 1; H318 Aquatic Chronic 1; H410	< 2.50 wt%
4	<b>3,6-bis(diethylamino)-9-[2-(methoxycarbonyl)phenyl]xanthylum tetrachlorozincate C.I. Basic Violet 11:1</b>		
	73398-89-7 277-459-0 - -	Acute Tox. 3; H331 Acute Tox. 3; H301 Aquatic Chronic 2; H411 Eye Dam. 1; H318	< 0.50 wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

**Acute toxicity estimate (ATE) values**

No	oral	dermal	inhalative
3	400 mg/kg bodyweight		

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**
**General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

**After inhalation**

Remove affected person from the immediate area. Ensure supply of fresh air.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners.

**After eye contact**

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Rinse out mouth and give plenty of water to drink. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

**Unsuitable extinguishing media**

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

**Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary).

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

### 7.2 Conditions for safe storage, including any incompatibilities

**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

**Requirements for storage rooms and vessels**

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

**Incompatible products**

Do not store together with: Acids; Alkalis; oxidizing agents

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Skin resorption / sensibilisation	Skin			
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
1-Methoxypropan-2-ol					
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Comments	Sk			
<b>2</b>	<b>hydrogen [tris[[[3-[(2-ethylhexyl)oxy]propyl]amino]sulphonyl]-29H,31H phthalocyaninesulphonato(3-)-N-{29}-,N-{30}-,N-{31}-,N-{32}]cuprate(1-), compound with 3-[(2-ethylhexyl)oxy]propylamine (1:1) C.I. Solvent Blue 70</b>	<b>94277-77-7</b>		<b>304-661-9</b>	
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Copper and compounds (as Cu) dusts and mists					
	WEL short-term (15 min reference period)	2	mg/m <sup>3</sup>		
	WEL long-term (8-hr TWA reference period)	1	mg/m <sup>3</sup>		

### DNEL, DMEL and PNEC values

#### DNEL values (worker)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	1-methoxy-2-propanol			<b>107-98-2</b> <b>203-539-1</b>
	dermal	Long term (chronic)	systemic	183 mg/kg/day
	inhalative	Long term (chronic)	systemic	369 mg/m <sup>3</sup>
	inhalative	Short term (acute)	local	553.5 mg/m <sup>3</sup>
	inhalative	Short term (acute)	systemic	553.5 mg/m <sup>3</sup>

#### DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	1-methoxy-2-propanol			<b>107-98-2</b> <b>203-539-1</b>
	oral	Long term (chronic)	systemic	33 mg/kg/day
	dermal	Long term (chronic)	systemic	78 mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9 mg/m <sup>3</sup>

#### PNEC values

No	Substance name			CAS / EC no
	ecological compartment	Type		Value
1	1-methoxy-2-propanol			<b>107-98-2</b> <b>203-539-1</b>
	water	fresh water		10 mg/L
	water	marine water		1 mg/L
	water	Aqua intermittent		100 mg/L
	water	fresh water sediment		52.3 mg/kg
	with reference to: dry weight			
	water	marine water sediment		5.2 mg/kg
	with reference to: dry weight			
	soil	-		4.59 mg/kg
	with reference to: dry weight			
	sewage treatment plant	-		100 mg/L

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator

A

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>	240	min

**Other**

Normal chemical work clothing.

**Environmental exposure controls**

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>			
liquid			
<b>Form</b>			
liquid			
<b>Colour</b>			
violet			
<b>Odour</b>			
characteristic			
<b>pH value</b>			
Value	appr.	5.2	
<b>Boiling point / boiling range</b>			
Value	appr.	110	°C
Reference pressure		1013	hPa
<b>Melting point/freezing point</b>			
No data available			
<b>Decomposition temperature</b>			
Value	>	200	°C
<b>Flash point</b>			
Value	appr.	31	°C
<b>Ignition temperature</b>			
No data available			
<b>Flammability</b>			
No data available			
<b>Lower explosion limit</b>			
No data available			
<b>Upper explosion limit</b>			
No data available			
<b>Vapour pressure</b>			
Value	<	110	kPa
Reference temperature		50	°C
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	appr.	0.956	g/cm <sup>3</sup>
Reference temperature		20	°C
<b>Solubility</b>			
No data available			
<b>Partition coefficient n-octanol/water (log value)</b>			
<b>No</b>	<b>Substance name</b>	<b>CAS no.</b>	<b>EC no.</b>
1	1-methoxy-2-propanol	107-98-2	203-539-1

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

log Pow	<	1	
Reference temperature		20	°C
with reference to	pH: 6.8		
Method	OECD 117		
Source	ECHA		

<b>Kinematic viscosity</b>			
Value	appr.	12	sec
Reference temperature		20	°C
Type	Efflux time		
Method	DIN cup 4 mm		

<b>Solvent separation test</b>			
Value	<	3	%
Reference temperature		20	°C

<b>Particle characteristics</b>			
No data available			

## 9.2 Other information

<b>Other information</b>
The physical data is that of the main component/s.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Formation of hydrogen gas upon contact with materials to avoid. Explosion hazard.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Moisture

### 10.5 Incompatible materials

Acids; Alkalis; Oxidizing agents

### 10.6 Hazardous decomposition products

Hydrogen

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity (result of the ATE calculation for the mixture)</b>	
<b>Product Name</b>	
edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
2	9-[2-(ethoxycarbonyl)phenyl]-3,6-bis(ethylamino)-2,7-dimethylxanthylium ethyl sulphate	26694-69-9	247-906-4
LD50		400	mg/kg bodyweight
Species	rat		
Source	manufacturer		

<b>Acute dermal toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		>	2000 mg/kg bodyweight

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

Species	rat
Method	440/2008/EC B.3.
Source	ECHA

**Acute inhalational toxicity (result of the ATE calculation for the mixture)**
**Product Name**
**edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300**
**Comments**

The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

**Acute inhalational toxicity**

No data available

**Skin corrosion/irritation**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species		rabbit	
Method		EC 440/2008, B.4	
Source		ECHA	
Evaluation		non-irritant	

**Serious eye damage/irritation**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species		rabbit	
Method		2004/73/EEC, B.5	
Source		ECHA	
Evaluation		non-irritant	

**Respiratory or skin sensitisation**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure		Skin	
Species		guinea pig	
Method		440/2008/EC B.6	
Source		ECHA	
Evaluation		non-sensitizing	

**Germ cell mutagenicity**

No data available

**Reproduction toxicity**

No data available

**Carcinogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Endocrine disrupting properties**

No data available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

**11.2 Information on other hazards**
**Other information**

No data available.

**SECTION 12: Ecological information**
**12.1 Toxicity**
**Toxicity to fish (acute)**

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LC50		> 4600	- 10000 mg/l
Duration of exposure			96 h
Species	Leuciscus idus		
Method	DIN 38 412, part L15		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### Toxicity to fish (chronic)

No data available

#### Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
EC50		21100	- 25900 mg/l
Duration of exposure			48 h
Species	Daphnia magna		
Method	ESR-ES-15		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### Toxicity to Daphnia (chronic)

No data available

#### Toxicity to algae (acute)

No data available

#### Toxicity to algae (chronic)

No data available

#### Bacteria toxicity

No data available

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value		96	%
Duration		28	day(s)
Method	OECD 301 E		
Source	ECHA		
Evaluation	readily biodegradable		

## 12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
log Pow		<	1
Reference temperature			20 °C
with reference to	pH: 6.8		
Method	OECD 117		
Source	ECHA		

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

### 13.1 Waste treatment methods

**Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN	UN1263
IMDG	UN1263
ICAO-TI / IATA	UN1263

### 14.2 UN proper shipping name

ADR/RID/ADN	PAINT
IMDG	PAINT
ICAO-TI / IATA	Paint

### 14.3 Transport hazard class(es)

<b>ADR/RID/ADN - Class</b>	3
Label	3
Classification code	F1
Tunnel restriction code	D/E
Hazard identification no.	30
<b>IMDG - Class</b>	3
Label	3
<b>ICAO-TI / IATA - Class</b>	3
Label	3

### 14.4 Packing group

ADR/RID/ADN	III
IMDG	III
ICAO-TI / IATA	III

### 14.5 Environmental hazards

EmS	F-E, S-E
-----	----------

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU regulations**

**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

**Trade name:** edding Permanent Ink (violet) contained in: edding 500, edding 3000, edding 3300

**Current version :** 2.1.0, issued: 04.06.2025

**Replaced version:** 2.0.0, issued: 04.06.2025

**Region:** GB

**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 792506