

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding 152 M, edding 153 B**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification information**

This product does not meet the classification and labelling criteria given in the Regulation (EC) No 1272/2008 (CLP).

### 2.2 Label elements

Not relevant

### 2.3 Other hazards

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	ethanol			
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225	>= 5.00 - < 10.00	wt%
2	propan-2-ol			

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

	67-63-0 200-661-7 603-117-00-0 -	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	< 5.00	wt%
3	<b>1-methoxy-2-propanol</b>			
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	< 5.00	wt%
4	<b>Additive B</b>			
	- - - -	Eye Irrit. 2; H319	< 5.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes and launder thoroughly before reusing.

#### After inhalation

Ensure supply of fresh air.

#### After skin contact

Wash immediately with plenty of water for several minutes.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam; Carbon dioxide; Extinguishing powder; Water spray jet

#### Unsuitable extinguishing media

No data available.

### 5.2 Special hazards arising from the substance or mixture

None known.

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Observe the usual precautions for handling chemicals.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of heat and ignition.

**7.2 Conditions for safe storage, including any incompatibilities**

**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place.

**Requirements for storage rooms and vessels**

Store product in closed containers.

**Incompatible products**

None known

**7.3 Specific end use(s)**

No data available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920	mg/m <sup>3</sup> 1000 ppm
2	propan-2-ol	67-63-0	200-661-7
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
	Propan-2-ol		
	WEL short-term (15 min reference period)	1250	mg/m <sup>3</sup> 500 ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m <sup>3</sup> 400 ppm
3	1-methoxy-2-propanol	107-98-2	203-539-1
<b>2000/39/EC</b>			
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
<b>List of approved workplace exposure limits (WELs) / EH40</b>			

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

1-Methoxypropan-2-ol					
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Comments	Sk			

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses (EN 166)

#### Hand protection

In case of intensive contact, wear protective gloves (EN 374). Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
red	
<b>Odour</b>	
weak	
<b>pH value</b>	
Value	7.4
<b>Boiling point / boiling range</b>	
Value	100 °C
Reference substance	Water
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Not applicable	
<b>Ignition temperature</b>	
No data available	
<b>Flammability</b>	
No data available	

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

<b>Lower explosion limit</b>	
No data available	
<b>Upper explosion limit</b>	
No data available	
<b>Vapour pressure</b>	
No data available	
<b>Relative vapour density</b>	
No data available	
<b>Relative density</b>	
Value	1.063
<b>Density</b>	
No data available	
<b>Solubility in water</b>	
Comments	soluble
<b>Solubility</b>	
No data available	
<b>Partition coefficient n-octanol/water (log value)</b>	
No data available	
<b>Kinematic viscosity</b>	
No data available	
<b>Particle characteristics</b>	
No data available	

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Heat; air humidity

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		6200	mg/kg bodyweight
Species		rat	

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

Source	Manufacturer
<b>2</b>   <b>propan-2-ol</b>	<b>67-63-0</b> <b>200-661-7</b>
LD50	5280 mg/kg bodyweight
Species	rat
Source	Manufacturer
<b>3</b>   <b>1-methoxy-2-propanol</b>	<b>107-98-2</b> <b>203-539-1</b>
LD50	5660 mg/kg bodyweight
Species	rat
Source	Manufacturer

<b>Acute dermal toxicity</b>			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>propan-2-ol</b>	<b>67-63-0</b>	<b>200-661-7</b>
LD50		12800	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		
<b>2</b>	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>	<b>203-539-1</b>
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

<b>Acute inhalational toxicity</b>			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>propan-2-ol</b>	<b>67-63-0</b>	<b>200-661-7</b>
LC50		72.6	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	Manufacturer		

<b>Skin corrosion/irritation</b>
No data available

<b>Serious eye damage/irritation</b>
No data available

<b>Respiratory or skin sensitisation</b>
No data available

<b>Germ cell mutagenicity</b>
No data available

<b>Reproduction toxicity</b>
No data available

<b>Carcinogenicity</b>
No data available

<b>STOT - single exposure</b>
No data available

<b>STOT - repeated exposure</b>
No data available

<b>Aspiration hazard</b>
No data available

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

## 11.2 Information on other hazards

### Endocrine disrupting properties

No data available.

### Other information

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		8150	mg/l
Duration of exposure		96	h
Species	Leuciscus idus		
Source	Manufacturer		
2	propan-2-ol	67-63-0	200-661-7
LC50		9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	Manufacturer		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		9268	mg/l
Duration of exposure		- 14221	h
Species	Daphnia magna		
Source	Manufacturer		
2	propan-2-ol	67-63-0	200-661-7
EC50		13299	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	Manufacturer		

Toxicity to Daphnia (chronic)			
No data available			

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
EC50		>	mg/l
Duration of exposure		1000	h
Species	Desmodesmus subspicatus		
Source	Manufacturer		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

### 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Value			%
Source	Manufacturer		
Evaluation	readily biodegradable		
2	propan-2-ol	67-63-0	200-661-7
Value		95	%
Duration		21	day(s)
Method	OECD 301 E		
Source	Manufacturer		

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

Evaluation	readily biodegradable
------------	-----------------------

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Endocrine disrupting properties

No data available.

### 12.7 Other adverse effects

No data available.

### 12.8 Other information

#### Other information

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

### 14.2 Transport IMDG

The product is not subject to IMDG regulations.

### 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

**Trade name:** edding OHP-Ink non-Permanent (red) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	3,4,5,6-tetrachloro-2-(1,4,5,8-tetrabromo-6-hydroxy-3-oxoxanthen-9-yl)benzoic acid C.I. Acid Red 92	18472-87-2	242-355-6	75
2	Disodium 2-(2,4,5,7-tetrabromo-6-oxido-3-oxoxanthen-9-yl)benzoate C.I. Acid Red 87	17372-87-1	241-409-6	75
3	hexachlorobenzene	118-74-1	204-273-9	75
4	propan-2-ol	67-63-0	200-661-7	75

#### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

## 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 19911