

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding Permanent Industriemarker Ink (blue) contained in: edding 8300**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Acute Tox. 4; H312

Acute Tox. 4; H332

Aquatic Chronic 3; H412

Eye Dam. 1; H318

Flam. Liq. 3; H226

Skin Irrit. 2; H315

STOT SE 3; H335

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS05



GHS07

**Signal word**

Danger

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

**Hazardous component(s) to be indicated on label:**

 m-xylene  
 2-methylpropan-1-ol

**Hazard statement(s)**

H226	Flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statement(s)**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	<b>m-xylene</b>		<b>pls. refer to footnote (1)</b>	
	108-38-3 203-576-3 601-022-00-9 01-2119484621-37	Acute Tox. 4; H312 Acute Tox. 4; H332 Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 50.00 - < 70.00	wt%
2	<b>2-methylpropan-1-ol</b>			
	78-83-1 201-148-0 603-108-00-1 -	Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	>= 10.00 - < 25.00	wt%
3	<b>4-(1,1,3,3-tetramethylbutyl)phenol</b>			
	140-66-9 205-426-2 604-075-00-6 -	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 Skin Irrit. 2; H315	< 0.50	wt%

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	-	-	M = 10	-

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

#### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

#### Incompatible products

None known

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	m-xylene	108-38-3	203-576-3
	2000/39/EC		
	m-Xylene		
	WEL short-term (15 min reference period)	442	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m <sup>3</sup> 50 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Xylene, o-, m-, p- or mixed isomers		
	WEL short-term (15 min reference period)	441	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m <sup>3</sup> 50 ppm
	Comments	Sk,BMGV	
2	2-methylpropan-1-ol	78-83-1	201-148-0
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	2-Methylpropan-1-ol		
	WEL short-term (15 min reference period)	231	mg/m <sup>3</sup> 75 ppm
	WEL long-term (8-hr TWA reference period)	154	mg/m <sup>3</sup> 50 ppm

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

3	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Comments	Sk	

### DNEL, DMEL and PNEC values

#### DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	m-xylene			<b>108-38-3</b> <b>203-576-3</b>	
	dermal	Long term (chronic)	systemic	212	mg/kg/day
	inhalative	Short term (acut)	local	442	mg/m <sup>3</sup>
	inhalative	Short term (acut)	systemic	442	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	local	221	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	221	mg/m <sup>3</sup>

#### DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	m-xylene			<b>108-38-3</b> <b>203-576-3</b>	
	oral	Long term (chronic)	systemic	2.5	mg/kg/day
	dermal	Long term (chronic)	systemic	125	mg/kg/day
	inhalative	Short term (acut)	local	260	mg/m <sup>3</sup>
	inhalative	Short term (acut)	systemic	260	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	local	65.3	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	65.3	mg/m <sup>3</sup>

#### PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	m-xylene		<b>108-38-3</b> <b>203-576-3</b>	
	water	fresh water	0.044	mg/L
	water	marine water	0.004	mg/L
	water	fresh water sediment	2.52	mg/kg dry weight
	water	marine water sediment	0.252	mg/kg dry weight
	soil	-	0.852	mg/kg dry weight
	sewage treatment plant	-	1.6	mg/L

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

**Eye / face protection**

Safety glasses with side protection shield (EN 166)

**Hand protection**

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

**Other**

Normal chemical work clothing.

**Environmental exposure controls**

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
blue	
<b>Odour</b>	
solvent-like	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	139 °C
Reference substance	CAS 108-38-3
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	27 °C
<b>Ignition temperature</b>	
No data available	
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
Value	1.1 % vol
Reference substance	CAS 108-38-3
<b>Upper explosion limit</b>	
Value	7.0 % vol
Reference substance	CAS 108-38-3
<b>Vapour pressure</b>	
Value	5 mm Hg
Reference temperature	20 °C
Reference substance	CAS 108-38-3

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

<b>Relative vapour density</b>	
No data available	
<b>Relative density</b>	
Value	0.9
<b>Density</b>	
No data available	
<b>Solubility in water</b>	
Comments	insoluble
<b>Solubility</b>	
No data available	
<b>Partition coefficient n-octanol/water (log value)</b>	
No data available	
<b>Kinematic viscosity</b>	
No data available	
<b>Solvent content</b>	
Value	72 %
<b>Particle characteristics</b>	
No data available	

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Heat

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	2-methylpropan-1-ol	78-83-1	201-148-0
LD50		2596	mg/kg bodyweight
Species	rat		
Source	manufacturer		

<b>Acute dermal toxicity (result of the ATE calculation for the mixture)</b>	
No	Product Name
1	edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

ATE (Mixture) Method	1718.75 mg/kg Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.
-------------------------	----------------------------------------------------------------------------------------------------------------------

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	2-methylpropan-1-ol	78-83-1	201-148-0
LD50		2523	mg/kg bodyweight
Species	rabbit		
Source	manufacturer		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding Permanent Industriemarker Ink (blue) contained in: edding 8300
ATE (Mixture)	17.1875 mg/l
Route of exposure / physical from	Vapour
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.

Acute inhalational toxicity
No data available

Skin corrosion/irritation
No data available

Serious eye damage/irritation
No data available

Respiratory or skin sensitisation
No data available

Germ cell mutagenicity
No data available

Reproduction toxicity
No data available

Carcinogenicity
No data available

STOT - single exposure
No data available

STOT - repeated exposure
No data available

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

## 11.2 Information on other hazards

### Endocrine disrupting properties

No data available.

### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish (acute)

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

No data available

**Toxicity to fish (chronic)**

No data available

**Toxicity to Daphnia (acute)**

No data available

**Toxicity to Daphnia (chronic)**

No data available

**Toxicity to algae (acute)**

No data available

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

**12.2 Persistence and degradability**

No data available.

**12.3 Bioaccumulative potential**

No data available.

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Endocrine disrupting properties**

No data available.

**12.7 Other adverse effects**

No data available.

**12.8 Other information**

**Other information**

Do not discharge product unmonitored into the environment.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

**SECTION 14: Transport information**

**14.1 UN number or ID number**

ADR/RID/ADN UN1263

IMDG UN1263

ICAO-TI / IATA UN1263

**14.2 UN proper shipping name**

ADR/RID/ADN PAINT

IMDG PAINT

ICAO-TI / IATA Paint

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

#### 14.3 Transport hazard class(es)

<b>ADR/RID/ADN - Class</b>	3
Label	3
Classification code	F1
Tunnel restriction code	D/E
Hazard identification no.	30
<b>IMDG - Class</b>	3
Label	3
<b>ICAO-TI / IATA - Class</b>	3
Label	3

#### 14.4 Packing group

<b>ADR/RID/ADN</b>	III
<b>IMDG</b>	III
<b>ICAO-TI / IATA</b>	III

#### 14.5 Environmental hazards

EmS	F-E, S-E
-----	----------

#### 14.6 Special precautions for user

No data available.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

##### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

The product contains following substance(s) meeting the criteria in Article 57 in association with Article 59 of the REACH regulation ((EC) 1907/2006) that are placed on the list of candidates considered for inclusion in annex XIV (substances subject to Authorisation).

No	Substance name	CAS no.	EC no.
1	4-(1,1,3,3-tetramethylbutyl)phenol	140-66-9	205-426-2

##### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-methylpropan-1-ol	78-83-1	201-148-0	75
2	4-(1,1,3,3-tetramethylbutyl)phenol	140-66-9	205-426-2	75
3	formaldehyde	50-00-0	200-001-8	75
4	m-xylene	108-38-3	203-576-3	75
5	toluene	108-88-3	203-625-9	75

##### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category: P5c

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

**Trade name:** edding Permanent Industriemarker Ink (blue) contained in: edding 8300

**Current version :** 4.1.0, issued: 27.02.2024

**Replaced version:** 4.1.0, issued: 14.04.2021

**Region:** GB

**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 25064